








- High efficiency stabilized power supplies
- Protection against short circuits
- Protection against overloads
- Cooling by free air convection
- Plate mounting: holes $\varnothing 3,5$ mm and M3
- ALI5/24DIN: Omega/DIN rail mounting

							
OUTPUT VOLTAGE	5 VDC $\pm 2\%$ 5 A	12 VDC $\pm 1\%$ 1.3 A	24 VDC $\pm 1\%$ 2.1 A	24 VDC $\pm 1\%$ 6.5 A	5 VDC $\pm 2\%$ 5.4 A	24 VDC $\pm 2\%$ 2 A	24 VDC $\pm 1\%$ 1 A
INPUT VOLTAGE (*selectable)	85 ÷ 264 VAC 47 ÷ 63 Hz	85 ÷ 132 VAC* 170 ÷ 264 VAC* 47 ÷ 63 Hz	85 ÷ 132 VAC* 170 ÷ 264 VAC* 47 ÷ 63 Hz	88 ÷ 132 VAC* 176 ÷ 264 VAC* 47 ÷ 63 Hz	85 ÷ 264 VAC 47 ÷ 63 Hz	85 ÷ 264 VAC 47 ÷ 63 Hz	100 ÷ 240 VAC 50 ÷ 60 Hz
OUTPUT POWER	25 W	15.6 W	50.4 W	156 W	25 W	48 W	24 W
DC ADJUSTMENT RANGE	-5% +10%	-10% +10%	-10% +10%	-12% +16%	-5% +10%	-6% +10%	-
WORKING TEMPERATURE	-10 °C +60 °C	-10 °C +60 °C	-10 °C +60 °C	-10 °C +60 °C	-10 °C +60 °C	-10 °C +60 °C	0 °C +40 °C
HUMIDITY (RH)	20% +90%	20% +90%	20% +90%	20% +90%	20% +90%	20% +90%	10% +90%
STORAGE TEMPERATURE	-20 °C +85 °C	-20 °C +85 °C	-20 °C +85 °C	-20 °C +85 °C	-20 °C +85 °C	-20 °C +85 °C	-30 °C +70 °C
HUMIDITY (RH)	10% +95%	10% +95%	10% +95%	10% +95%	10% +95%	10% +95%	10% +90%
FIXED SWITCHING FREQUENCY	37 Hz	37 Hz	27 Hz	25 Hz	37 Hz	37 Hz	-
DIMENSIONS	100x97x38 mm	100x97x38 mm	160x97x38 mm	200x110x50 mm	93x78x67 mm	93x78x67 mm	89x74x34 mm
WEIGHT	390 g	310 g	510 g	800 g	310 g	310 g	300 g
CODE	ALIM5P190	ALI12STAB	ALI24STAB	ALI24STAB6A	ALI5DIN	ALI24DIN	ALI24SPINA1A ALI24SPINA1AJACK