










	DESCRIPTION	CODE
CABLES AND SHEATHES		
	6x0.22 mm ² shielded cable. Available coils: 5 - 10 - 200 m.	CAVO6020S
	6x0.22 mm ² anti-rodent armored shielded cable. Available coils: 5 - 10 - 200 m.	CAVO6020SARM
	PVC flexible sheath, installed on the load cell cable. IP67 - inner Ø: 10 mm - outer Ø: 14 mm. <ul style="list-style-type: none"> ■ length 3 m + 1 PVC end-fitting ■ length 5 m + 1 PVC end-fitting ■ length 6 m + 1 PVC end-fitting ■ length 10 m + 1 PVC end-fitting 	GUA3 GUA5 GUA6 GUA10
	6x0.22 mm ² shielded extension cable, sheathed, for connecting the weighing instrument to the junction box. PVC flexible sheath - IP67. Wiring by the customer. <ul style="list-style-type: none"> ■ length 5 m + 1 PG9 PVC end-fitting ■ length 10 m + 1 PG9 PVC end-fitting 	ESTENSIONE5 ESTENSIONE10
WIRINGS		
	Wiring between load cell and junction box.	COLCELLA
	Wiring between weighing instrument and junction box.	COLSTRU
SELECTOR SWITCHES		
	External 12-position selector switch for selecting formulas and setpoint groups.	EC